



## QUALITY WATER CARE

Integrated features ensure the cleanest, clearest water with minimal effort from you.

- 1** Fill hot tub through primary filtration side to just above the highest jet.
- 2** Test your water for pH and total alkalinity using the Aqua Check test strips provided. Adjust your water accordingly. When balancing, always adjust alkalinity before pH.
  - \*Make sure pump 1 is running in high speed when adding chemicals\***
  - pH 7.2 - 7.8 Alkalinity 100 - 140ppm**
  - Raise alkalinity if required using Jacuzzi® Alka Up
    - 1 cap of Jacuzzi® Alka Up will raise alkalinity 10ppm
  - Lower alkalinity if required using Jacuzzi® pH Down
    - 1 cap of Jacuzzi® pH Down will lower alkalinity 10ppm (For example, if alkalinity is 180ppm you will need to add 4 caps of Jacuzzi® pH Down to 140ppm)
  - Add no more than 3 caps of Jacuzzi® pH Down or Jacuzzi® Alka Up in a 20 minute period**
  - Adjust pH only if necessary
    - 1 cap of Jacuzzi® pH Down will lower the pH one colour shade on the test strip bottle.
- 3** Install Jacuzzi® ProClear® Mineral Cartridge as directed. Tie Zorbie to filter grate or place inside ProCatch™ bag if equipped.
- 4**
  - Add 6 tablespoons of Stain & Scale
  - Add 1 tablespoon of Chlorine Granules
  - Add 6 caps of Ultra Spa
- 5** Run pump 1 on high speed for 20 minutes with hot tub cover open and retest; be sure to monitor your hot tub for safety while cover is open.
- 6** Once temperature reaches 90F add entire bottle of Spa Solution and run pump 1 on high speed for 20 minutes with the cover open.



For owners resources or to schedule service, visit:  
[www.jacuzziontario.com](http://www.jacuzziontario.com)



Visit [www.hottubstore.ca](http://www.hottubstore.ca)  
to replenish your water care products

# Water Care Plan

## AFTER EACH USE



- Turn air controls to the off position
- Add 1 tablespoon of Chlorine Granules and 1 cap of Spa Shock. Run pump on high speed for 20 minutes with hot tub cover open
- Repeat above step for heavier use

## ONCE A WEEK



- Test your pH & Total Alkalinity using test strips - Adjust your water accordingly
- Add 3 tablespoons of Stain & Scale
- Add 1 tablespoon of Chlorine Granules
- Add 1 cap of Spa Shock
- Add 2 caps of Ultra Spa

## ONCE A MONTH



- Rinse and clean filters using Aqua Magic Cartridge Cleaner and a Filter Flosser

## EVERY 4 MONTHS



- If required drain and refill your hot tub
- Replace your Jacuzzi® ProClear® Mineral Cartridge, Zorbie & add Spa Solution
- If equipped, replace your Jacuzzi® ProClarity® Depth Load Filter
- Clean the cover, cabinet & steps

## ONCE A YEAR



- Replace your CLEARARRAY® UV-C Bulb

## EVERY 2 YEARS



- Inspect your CLEARARRAY® PRO<sub>3</sub>TECT™ Automatic Oxidizer